

LRC-L1

CATTRONCONTROL™



FULL-SIZED, HIGHLY CUSTOMIZABLE CONTROLLER

HIGHLIGHTS

Wide range of control options including:

- up to three stepped or stepless joysticks
- up to five full-size paddles
- up to eight mini paddles
- up to 32 auxiliary switches
- up to 10 additional control elements such as push buttons, toggles and rotary switches
- System configuration via a secure wireless
- Transkey™ (RFID) for simple spares management
- Customer-specific layout with a wide range of control elements
- Approvals and frequencies for worldwide deployment

FEATURES

- Used for the control of cranes and machines with digital, Bus or analog drive systems
- Graphic LCD and LEDs for status and feedback
- High safety level through redundant hardware and software architecture
- IP65 housing made of impact-resistant nylon for tough indoor or outdoor environments
- Compatible with all CT24, CCM12 and MMCU4 machine control units
- Optional tilt detection safety feature
- Tandem and multi-transmitter and/or receiver operation
- Optional SymmetryLock™ crane interlocking and multi-MCU Talkback

APPLICATIONS

This tough full-size, and highly configurable controller is ideal for operation in almost any application.

- Overhead Cranes
- Machine Control
- Ship Loaders
- Metal Fabrication
- Amusement Parks
- Lifting Equipment

COMPLIANCE

- EN 13849-1 Category 3 PL d
- EN 60204-1
- EN 60204-32
- CE Compliant





TECHNICAL DATA AND SPECIFICATIONS

ELECTRONIC DATA

Commands	Up to 55 digital commands + STOP Up to 8 analog commands
Digital Circuitry	Dual-processor Technology
System Addresses	24 bits = 16 million addresses
Energy-Saving Mode	Automatic shutdown (configurable 0-30 minutes)
Supply Voltage	Rechargeable battery, NiMH 4.8V/1600 mAh
Battery Life	> 12 h at 100% uninterrupted use

OPERATION AND INDICATION

Layout	Standard 2 joysticks or fully customizable
Control Elements (typical)	2 joysticks, stepped or step-less, start, horn, stop, keyswitch, push buttons, toggled switches, rotary switches, etc.
Transkey™	System configuration, address and RF channel setting
Buzzer	Low voltage indication and tilt
Graphics LCD	128 x 32 dots, backlight white (graphic LCD optional)
LED	1 status LED 4 multi-function LEDs

MECHANICAL DATA

Weight	Approx. 1.7 to 2.3 kg (3.7 to 5 lbs)
Dimensions L x W x H	370 x 200 x 175 mm (14.8 x 7.8 x 7 inches)
Housing	Nylon, standard color red/gray IP65, suitable for outdoor use
Operating Temperature	-20° to +60° C (-4° to +140° F)
Vibration and Shock	Vibration/impact and drop tested to 1m on concrete

RF

Frequency Range	335 MHz 406-419 MHz 433-434 MHz 447-473 MHz 869 MHz 902-927 MHz Other frequencies possible
Transmitter Power	10-500 mW
Regulatory	Licensed and unlicensed bands available
RF Security	Black Channel
RF Channel Spacing	12.5 kHz; 25 kHz and others
Antenna	Internal

ACCESSORIES

Batteries	2 rechargeable batteries, NiMH, 4.8 V/1600 mAh
Battery Charger	Processor-controlled charger with changing system on the primary side for international use 100-240 V AC, 50-60 Hz

North America: +1.234.806.0018 | Sales.US@Cattron.com
 Europe: +49.2151.4795.0 | Sales.EU@Cattron.com
 UK: +44.1932.238121 | Sales.UK@Cattron.com
 South America: +55.19.3518.7030 | Sales.BR@Cattron.com
 Asia: Sales.CN@Cattron.com

cattron.com

LRC-L1_EN_201902



Any information furnished by Cattron™ and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Cattron products rests with the end user since Cattron and its agents cannot be aware of all potential uses. Cattron makes no warranties as to non-infringement nor as to the fitness, merchantability, or sustainability of any Cattron products for any specific or general uses. Cattron Holdings, Inc., or any of its affiliates or agents shall not be liable for incidental or consequential damages of any kind. All Cattron products are sold pursuant to the Terms and Conditions of Sale, a copy of which will be furnished upon request. When used as a trademark herein, Cattron means Cattron Holdings, Inc. or one or more subsidiaries of Cattron Holdings, Inc. Cattron™, corresponding logos, and other marks are trademarks or registered trademarks of Cattron Holdings, Inc. Other marks may be the property of third parties. Nothing herein provides a license under any Cattron or any third party intellectual property right.