

LRC-M1

CATTRONCONTROL™



MID-SIZED CONTROLLER, STANDARD AND CUSTOMIZABLE

HIGHLIGHTS

Wide range of control options including:

- up to two stepped or stepless joysticks
- up to three full-size paddles
- up to six mini paddles
- up to 22 auxiliary switches
- horn/STOP/ON-OFF
- System configuration via a secure wireless
- Transkey™ (RFID) for simple spares management
- Customer-specific layout with a wide range of control elements
- Approvals and frequencies for worldwide deployment

FEATURES

- Used for the control of cranes and machines with Bus, digital or analog drive systems
- Graphic LCD and LEDs for status and feedback
- High safety level through redundant hardware and software architecture
- IP65 housing made of impact-resistant nylon for tough indoor or outdoor environments, excellent chemical and oil resistivity and superior mechanical strength
- Compatible with all CT24, CCM12 and MMCU4 machine control units
- Optional tilt detection safety feature
- Tandem and multi-transmitter and/or receiver operation
- Optional SymmetryLock™ crane interlocking and multi-MCU Talkback™

APPLICATIONS

This tough mid-size, and highly configurable controller is ideal for operation in almost any application.

- Overhead Cranes
- Machine Control
- Ship Loaders
- Metal Fabrication
- Amusement Parks
- Lifting Equipment

COMPLIANCE

- EN 13849-1 Category 3 PL d
- EN 60204-1
- EN 60204-32
- CE Compliant





TECHNICAL DATA AND SPECIFICATIONS

ELECTRONIC DATA

Commands	Up to 34 digital commands + STOP Up to 8 analog commands
Digital Circuitry	Dual-processor Technology
System Addresses	24 bits = 16 million addresses
Energy-Saving Mode	Automatic shutdown (configurable 0-30 minutes)
Battery	Rechargeable, NiMH 4.8V/1600 mAh
Battery Life	> 12 h at 100% uninterrupted use

OPERATION AND INDICATION

Layout	Standard 2 joysticks or fully customizable
Control Elements (typical)	2 joysticks, stepped or stepless, start, horn, stop, keyswitch, push buttons, toggled switches, rotary switches, etc.
Transkey™	System configuration, address and RF channel setting
Buzzer	Low voltage indication and tilt
Graphics LCD	128 x 32 dots, backlight white (graphic LCD optional)
LED	1 status LED 4 multi-function LEDs

MECHANICAL DATA

Weight	Approx. 1.6 kg (3.5 lbs)
Dimensions L x W x H	274 x 207 x 160 mm (10.8 x 8.2 x 6.3 inches)
Housing	Nylon, standard color red/gray IP65, suitable for outdoor use
Vibration and Shock	Vibration/impact and drop tested to 1m on concrete

RF

Frequency Range	335 MHz 406-419 MHz 433-434 MHz 447-473 MHz 869 MHz 902-927 MHz Other frequencies possible
Regulatory	Licensed and unlicensed bands available
Transmitter Output Power	10-500 mW
RF Security	Black Channel
RF Channel Spacing	12.5 kHz; 25 kHz and others
Antenna	Internal

ACCESSORIES

Batteries	2 rechargeable batteries, NiMH, 4.8 V/1600 mAh
Battery Charger	Processor-controlled charger with changing system on the primary side for international use 100-240 V AC, 50-60 Hz

North America: +1.234.806.0018 | Sales.US@Cattron.com
Europe: +49.2151.4795.0 | Sales.EU@Cattron.com
UK: +44.1932.238121 | Sales.UK@Cattron.com
South America: +55.19.3518.7030 | Sales.BR@Cattron.com
Asia: Sales.CN@Cattron.com

cattron.com

LRC-M1_EN_201902

Any information furnished by Cattron™ and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Cattron products rests with the end user since Cattron and its agents cannot be aware of all potential uses. Cattron makes no warranties as to non-infringement nor as to the fitness, merchantability, or sustainability of any Cattron products for any specific or general uses. Cattron Holdings, Inc., or any of its affiliates or agents shall not be liable for incidental or consequential damages of any kind. All Cattron products are sold pursuant to the Terms and Conditions of Sale, a copy of which will be furnished upon request. When used as a tradename herein, Cattron means Cattron Holdings, Inc. or one or more subsidiaries of Cattron Holdings, Inc. Cattron™, corresponding logos, and other marks are trademarks or registered trademarks of Cattron Holdings, Inc. Other marks may be the property of third parties. Nothing herein provides a license under any Cattron or any third party intellectual property right.

