

Fissaid® Anti-copy Standalone controller

Description:

AC-8003 accepts read only EM4100 or compatible RFID card and will reject any card made by writable chip such as T5577 EM4305 etc. It is standalone access controller with 3*4 keypad and 1000 users capacity. The controller accepts up to 1000 users and provides entry via the user of proximity cards and/or PIN codes.

The product has strong functions and advantages such as low power consumption, independent passwords, External prox + PIN code keypad wiegand input, exit button, which is widely used at home, office, residential area and other high secure places. Anti-copy card function make access control system much secure.

Model/Picture and Wiring

	Model:	AC-8003
	Wiring:	Red: Power 9-15V
		Black: Power ground
		Yellow: Release button
		Green: Wiegand input D0
		White: Wiegand input D1
		Blue: Relay output terminal NC
		Purple: Relay output terminal NO
	Gray: Relay output terminal COM	

Features

1000 user capacity
Door release time adjustable from 1-255s
Open door with 4 models: PIN only, Prox only, Prox+PIN, Release button from inside
Enrol/delete card by keypad, or master card
Delete card by input card number from keypad directly
Relay Outputs: Door Relay Form C, 3A/30VDC
Controller is with an external wiegand26 reader input interface, So unit can be installed inside with an external proximity card reader or keypad installed outside of the region to make controller system much securer.

Specification:

DC power input	9-15VDC at 100mA, A linear regulator is recommended
Support card	125KHz EM4100 or compatible read only ID card
Interface	Wiegand for external keyboard or reader input
Read range	3-6 cm
Frequency	122-128KHz
Operating temperature	-30°C to +60°C
Operating humidity	5%-95% (non-condensing)
Audio/Visual Indication	Green & Red LED and Buzzer signal output
Response Time	Less than 0.2 seconds
size	98*90*22mm
Weight	150 gram
Cable	8 pin /250mm

Master card

Controller accepts two type master card which are "ADD card" and "Delete Card", unit manager may create those cards and use them to enroll or delete registered user fastly

Anti-copy:

Controller will automaticall distinguish the copied EM card (such as card made by T5577/EM4305 etc)